



# ROLLCLIP A

Pulley-carabiner that facilitates installation of the rope when pulley is connected to the anchor.

ROLLCLIP A is a pulley-carabiner with a gate opening on the pulley side that facilitates installation of the rope when the pulley is fixed to the anchor. It is available with an automatic TRIACT-LOCK locking system, or without a locking system. ROLLCLIP A may be used with a CAPTIV positioning bar to favor loading of the carabiner along the major axis, to limit the risk of it flipping and to keep it integrated with the device.

## Detailed description

- Easier handling:
  - sheave mounted on sealed ball bearings for excellent efficiency
  - gate opening on the pulley side facilitates installation of the rope when the pulley is fixed to the anchor
  - may be used with a CAPTIV positioning bar to favor loading of the carabiner along the major axis and to limit the risk of it flipping
  - Keylock system prevents any accidental snagging of the carabiner when putting the pulley in place.
- H cross-section of carabiner:
  - ensures an improved strength-to-weight ratio
  - protects markings from abrasion
- Available in versions with or without TRIACT-LOCK locking system

## Specifications

- Material(s): aluminum
- Min. rope diameter: 7 mm
- Max. rope diameter: 13 mm
- Sheave diameter: 18 mm
- Maximum working load:  $2 \times 2 = 4$  kN
- Efficiency: 85 %
- Major axis strength: 20 kN
- Minor axis strength: 8 kN
- Open gate strength: 7 kN
- Guarantee 3 years