



ROLLCLIP Z

Pulley-carabiner that facilitates installation on anchors and devices

ROLLCLIP Z is a pulley-carabiner with a gate opening on the non-pulley side to facilitate installation on anchors and devices. It is available in two locking systems: automatic TRIACT-LOCK system or manual SCREW-LOCK system.

Detailed description

- Easier handling:
 - sheave mounted on sealed ball bearings for excellent efficiency
 - gate opening on the non-pulley side, to facilitate installation on devices
 - Keylock system prevents any accidental snagging of the carabiner when putting the pulley in place
- H cross-section of carabiner:
 - ensures an improved strength-to-weight ratio
 - protects markings from abrasion
- Two locking systems available:
 - TRIACT-LOCK: automatic locking with triple-action gate opening
 - SCREW-LOCK: the manual screw-lock with red band provides a visual warning when the carabiner is unlocked.

Specifications

- Material(s): aluminum
- Min. rope diameter: 7 mm
- Max. rope diameter: 13 mm
- Sheave diameter: 18 mm
- Maximum working load: $2 \times 2 = 4$ kN
- Efficiency: 85 %
- Major axis strength: 20 kN
- Minor axis strength: 8 kN
- Open gate strength: 7 kN
- Guarantee 3 years